

TWP MILDEW SEALER

Page: 1

PRODUCT NAME: TWP MILDEW SEALER  
PRODUCT CODE: TWP MILDEW SEALER

HMIS CODES: H F R P  
1 0 0 C

=====  
SECTION I - MANUFACTURER IDENTIFICATION  
=====

MANUFACTURER'S NAME: AMTECO, INC.

ADDRESS : P.O. BOX 9  
1100 JEFFERSON ST  
PACIFIC, MO. 63069

EMERGENCY PHONE : 1-800-424-9300 DATE PRINTED : 03/19/03

INFORMATION PHONE : 1-800-827-3480 NAME OF PREPARER : N/A

=====  
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION  
=====

VAPOR PRESSURE

WEIGHT

REPORTABLE COMPONENTS  
PERCENT

CAS NUMBER mm Hg @ TEMP

-----  
AQUEOUS ACRYLIC EMULSION

ESTER ALCOHOL  
NE

25265-77-41 87 C

N/A

PAINT, NON HAZARDOUS - NOT REGULATED

=====  
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS  
=====

BOILING RANGE: 244 C

SPECIFIC GRAVITY (H2O=1): 1.03

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 1.72 lb/gl

MATERIAL V.O.C.: 0.50 lb/gl

SOLUBILITY IN WATER: SOLUBLE

APPEARANCE AND ODOR:

=====  
SECTION IV - FIRE AND EXPLOSION HAZARD DATA  
=====

FLASH POINT: 248 F

METHOD USED: COC

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1

UPPER: 4

EXTINGUISHING MEDIA: USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

SPECIAL FIREFIGHTING PROCEDURES

THIS PRODUCT WILL NOT SUPPORT COMBUSTION

UNUSUAL FIRE AND EXPLOSION HAZARDS

MATERIAL CAN SPLATTER ABOVE 100C/212F. DRIED PRODUCT CAN BURN.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE  
CONDITIONS TO AVOID  
NONE KNOWN

INCOMPATIBILITY (MATERIALS TO AVOID)  
NONE KNOWN

HAZARDOUS DECOMPOSITION OR BYPRODUCTS  
CARBON DIOXIDE, CARBON MONOXIDE, OXIDES OF NITROGEN

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
INHALATION OF VAPOR OR MIST CAN CAUSE HE FOLLOWING:

TWP MILDEW SEALER

Page: 2

HEADACHE-NAUSEA-IRRITATION OF NOSE, THROAT AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
EYE CONTACT-DIRECT CONTACT MAY CAUSE SLIGHT IRRITATION AND DRYNESS.  
SKIN CONTACT-PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD IRRITATION AND DRYNESS.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
PROLONGED OR REPEATED SKIN CONTACT CAN CAUSE MILD IRRITATION AND DRYNESS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE  
MAY CAUSE NAUSEA AND VOMITING.

HEALTH HAZARDS (ACUTE AND CHRONIC)  
NOT KNOWN

CARCINOGENICITY: NTP CARCINOGEN: N/A IARC MONOGRAPHS: N/A OSHA REGULATED: N/A  
N/A

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE  
NOT KNOWN

EMERGENCY AND FIRST AID PROCEDURES  
INHALATION: MOVE SUBJECT TO FRESH AIR. RESTORE BREATHING IF NECESSARY. TREAT SYMPTOMATICALLY AND CONSULT PHYSICIAN. EYE & SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNT OF WATER FOR ATLEAST 15 MINUTES. SEE A PHYSICIAN IMMEDIATELY. WASH SKIN AFTER REMOVING CONTAMINATED CLOTHING WITH MILD SOAP AND WATER FOR 15 MINUTES. SEE PHYSICIAN IF IRRITATION PERSISTS. INGESTION: DRINK 1-2 GLASSES OF WATER TO

DILUTE. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY. TREAT SYMPTOMATICALLY. NEVER GIVE LIQUIDS TO AN UNCONSCIOUS PERSON.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
KEEP SPECTATORS AWAY. FLOOR MAY BE SLIPPERY; USE CARE TO AVOID FALLING. CONTAIN SPILLS IMMEDIATELY WITH INER MATERIALS (E.G. SAND, EARTH). TRANSFER LIQUIDS AND SOLID DIKING MATERIAL TO SEPARATE SUITABLE CONTAINERS FOR RECOVERY OR DISPOSAL.

WASTE DISPOSAL METHOD  
DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING  
KEEP FROM FREEZING.

OTHER PRECAUTIONS  
DO NOT TAKE INTERNALLY

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION  
A RESPIRATORY PROTECTION PROGRAM MEETING OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. NONE REQUIRED IF AIRBORNE CONCENTRATIONS ARE MAINTED BELOW THE EXPOSURE LIMIT LISTED IN "EXPOSURE LIMIT INFORMATION", WEAR A MSHA/NIOSH APPROVED (OR EQUIVALENT) HALF-MASKED, AIR-PURIFYING RESPIRATOR. IF NO EXPOSURE LIMITS ARE LISTED, THAN NO RESPIRATOR IS NEEDED.

VENTILATION  
USE LOCAL EXHAUST VENTILATION WITH A MINIMUM CAPTURE VELOCITY OF 100 FT/MIN. (0.5 M/SEC.) AT THE POINT OF VAPOR EVOLUTION.

PROTECTIVE GLOVES  
NEOPRENE GLOVES RECOMMENDED FOR DIRECT CONTACT.

TWP MILDEW SEALER

Page: 3

EYE PROTECTION  
USE CHEMICAL SPLASH GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT  
FACILITIES STORING OR UTILIZING THIS MATERIAL SHOULD BE EQUIPPED WITH AN EYE WASH STATION AND SHOWER.

WORK/HYGIENIC PRACTICES  
WASH HANDS BEFORE AND AFTER EATING, SMOKING AND USING THE BATHROOM.

===== SECTION IX - DISCLAIMER =====

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE.  
HOWEVER, AMTECO, INC. DOES NOT ASSUME ANY LIABILITY WHATSOEVER FOR THE ACCURACY  
OF COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF  
SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER.

