

# MATERIAL SAFETY DATA SHEET

Wood Care Systems

715 Kirkland Avenue

Kirkland, WA 98033

## SECTION I - PRODUCT IDENTIFICATION

Product Name: **Timbr Flex Putty (PART B)**  
MSDS Number: TFB  
Product Type: Epoxy Hardener  
**24-hr. Emergency Phone:**  
**Call Chemtrec: (800) 424-9300**

Date of Prep: 5/06/00  
Previous Revision: None  
Reason Revised: New Product  
Information: (206) 782-7976  
Prepared By: J. Renfroe

**Hazard Ratings:**  
**Health 3**  
**Fire 1**  
**Reactivity 0**

## SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

HAZARDOUS COMPONENTS	AMOUNT	CAS NUMBER	OSHA PEL	ACGIH TLV
Polyamide Polymer	70-90%	Trade Secret	not established	not established
Nonyl Phenol	5-10%	25154-52-3	none established	not established
Benzyl Alcohol	1-5%	100-51-6	none established	not established

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Range: N/A  
Vapor Density: Heavier than Air  
Evaporation Rate: Slower than Ether  
Appearance and Odor: Tan, clay-like paste with mild ammonia smell. Dead air space above liquid in containers may have strong ammonia smell.

Specific Gravity: 0.97  
Material V.O.C.: None  
Water Solubility: Negligible

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: > 250F° Method: Pensky-Martins Closed Cup  
Flammable Limits in Air By Volume: Lower: N/A Upper: N/A  
Extinguishing Media: Foam, Carbon Dioxide, Dry Chemical, Water Fog

### Special Firefighting Procedures:

When fighting chemical fires wear full protective equipment with self-contained breathing apparatus. Water spray may be used to cool fire exposed containers. Toxic fumes will be evolved when this substance is burned.

## SECTION V - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Epoxy resins and epoxy resin hardeners react with each other producing heat. They should not be mixed with each other under uncontrolled conditions or in large mass as the ensuing exotherm may result in heat and smoke.

Incompatibility: Strong oxidizing agents, mineral acids.

Hazardous Decomposition Products: Oxides of carbon, nitrogen

Hazardous Polymerization: Will not occur.

## SECTION VI - HEALTH HAZARD DATA

### EFFECTS OF OVEREXPOSURE:

Acute: May cause burns to skin and eyes. High vapor concentration can cause severe irritation of eyes and respiratory tract. Liquid causes severe damage to mucous membranes if swallowed.

Chronic: Prolonged and repeated skin contact may cause skin sensitization, asthma or other allergic responses.

Carcinogenicity: Results of in vitro mutagenicity tests on polyamides have been negative. It is not expected that any of the ingredients are carcinogenic.

#### EMERGENCY AND FIRST AID PROCEDURES:

Eyes: Flush thoroughly with water for at least 15 minutes. Get immediate medical attention.

Skin: Remove contaminated clothing and flood area with water. Wash affected skin with soap and water. Wash clothing before reuse. Discard shoes. Get medical attention if redness, soreness, or blistering occur or persist.

Inhalation: Remove to fresh air. Administer oxygen if necessary. Get medical attention if breathing is difficult or cough develops.

Ingestion: DO NOT INDUCE VOMITING. Vomiting will cause further damage to throat or respiratory tract. Dilute by giving water or milk to drink if victim is conscious. GET IMMEDIATE MEDICAL ATTENTION.

Medical Conditions Generally Aggravated by Exposure: This material may be a strong skin sensitizer in certain susceptible persons. Once sensitized, most persons are unable to work around amine cured epoxy resins without an allergic reaction. Sensitized persons are not known to have other health problems as a result of sensitization.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

If Material is Spilled: Avoid contact with material. Persons not wearing appropriate protective equipment should leave the area of the spill until cleanup is complete. Stop spill at source, dike area to prevent spreading, pump liquid to salvage tank or drum. Remaining liquid may be taken up on clay, diatomaceous earth, sawdust, or other absorbant, and shoveled into disposal containers.

Waste Disposal Method: Waste is not hazardous by RCRA criteria. (40 CFR 261). Place in an appropriate disposal facility in compliance with local regulations.

### SECTION VIII - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Normally none is required when adequate ventilation is provided. In the absence of proper environmental control NIOSH approved respiratory is required. For emergencies, a self-contained breathing apparatus or full-faced respirator is recommended.

Ventilation: Provide adequate ventilation in work areas. Confine material in sealed containers when not in use.

Hand Protection: Always wear impervious gloves, neoprene, vinyl or rubber.

Eye Protection: Splash proof goggles or safety spectacles with side shields are recommended. Always wear eye protection when sanding cured epoxy resins to avoid dust in eyes.

Other Protective Equipment: Wear clean, body-covering clothing to avoid skin contact.

### SECTION IX - TRANSPORTATION REQUIREMENTS

Department of Transportation Classification: Not Hazardous D.O.T. Proper Shipping Name: Not Regulated

#### Other Requirements:

This product contains no toxic chemicals subject to the report requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

---

The information contained herein is based on the data available to us and is believed to be correct. However, Wood Care Systems makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof. Wood Care assumes no responsibility for injury from the use of the product described herein.